



XAVIER II 5.6KW

PURE SINE WAVE SOLAR MPPT BASED INVERTER

PV - 6000

PRODUCT KEY FEATURES

- 👑 Pure sine wave solar MPPT based inverter
- 👑 Wide PV input voltage range 60VDC~450VDC
- 👑 Battery independent design
- 👑 Maximum PV input current, 27A
- 👑 Feed-in to the grid function
- 👑 Battery equalization function to optimize battery performance and extend life cycle
- 👑 Built-in 120A Mppt solar charger
- 👑 Dual output, for smart load management
- 👑 Output power factor 1
- 👑 RGB Crown logo



Technical Data

MODEL NAME	XAVIER-II-5.6KW
RATED POWER	5600VA/5600W
INPUT	
Voltage	230VAC
Selectable voltage range	170 ~ 280VAC (for personal computers) 90 ~ 280VAC (for home appliances)
Frequency range	50 Hz / 60 Hz (auto sensing)
OUTPUT	
AC voltage regulation (batt. mode)	230VAC ± 5%
Surge power	11200VA
Efficiency (peak)	93%
Transfer time	10ms (for personal computers), 20ms (for home appliances)
Waveform	Pure sine wave
Dual output	Yes
BATTERY	
Battery voltage	48VDC
Floating charge voltage	54VDC
Overcharge protection	63VDC
SOLAR CHARGER & AC CHARGER	
Solar charger type	MPPT
Max. PV array open circuit voltage	500VDC
Max. PV array power	6000W
Max. PV input current	27A
MPPT range @ operating voltage	60 ~ 450VDC
Max. solar charge current	120A
Max. AC charge current	100A
Max. charge current	120A
GENERAL SPECIFICATION	
Dimension, D*W*H (mm)	107*322.6*20.3
Net weight (Kgs)	10.5
Communication interface	USB/RS-232 (optional USB / dry contact)
OPERATING ENVIRONMENT	
Humidity	5% to 95% relative humidity (non-condensing)
Operating temperature	-10°C to 50°C
Storage temperature	-15°C to 60°C